

# Pipemate™



Accurate square and bevel edge circumferential flame cutting. Designed for simple operation with optimum stability and a smooth dependable drive, the Pipemate™ is fully adjustable to any cutting length. The control valves are located away from the heat and changeover is quick between differing diameters.

## Ordering Information

Part No.	Description
338534	Pipemate™ includes acetylene nozzle size 1, tip cleaners, spanners and chain 2.4m

### Parts & Accessories

Part No.	Description
----------	-------------

#### 3 Seat cutting nozzles - standard speed Acetylene

306114	Tip size 00, 0-5mm plate thickness
306115	Tip size 0, 5-10mm plate thickness
306116	Tip size 1, 10-15mm plate thickness
306117	Tip size 2, 15-30mm plate thickness
306118	Tip size 3, 30-40mm plate thickness
306119	Tip size 4, 40-50mm plate thickness

#### 3 Seat cutting nozzles - standard speed LP gas

306097	Tip size 0, 5-10mm plate thickness
306098	Tip size 1, 10-15mm plate thickness
306099	Tip size 2, 15-30mm plate thickness
306100	Tip size 3, 30-40mm plate thickness
306101	Tip size 4, 40-50mm plate thickness

333094	Additional 2m chain
OKS5020	Nozzle nut

## Specifications

Pipe diameter	Pipe Wall Thickness	Weight
100-600mm	up to 50mm	9kg